

# Introducing the Newest Member of the Powerhouse® Family . . . PH6500Ri Inverter Generator Maximum Power at an Affordable Price.

The PH6500Ri Inverter Generator is designed with the professional tradesman and high-demand recreational user in mind. It delivers 6000 watts of continuous power and 6500 watts of maximum power. Ideal for running high demand tools and equipment from compressors to welders or as a central power supply for multiple users of hand power tools. It's inverter equipped making it safe for use with sensitive electronic equipment like lap tops and cell phones.

The PH6500Ri has remarkable functionality and comes with great features at an affordable price. Standard features include remote electric start, a 120/240 V switch, four power outlets and a 12 V utility connection. It has a powerful 11.6 hp engine and can run up to 12.8 hours on a single tank of gas.


PH6500RI Control Panel



30 Amp  
120V Outlet

120V/240V  
Switch

50 Amp  
120V Twist  
Outlet



Remote start from  
up to 75 feet away.

## POWERHOUSE® INVERTER GENERATORS



Remote Electric start from up to 75 feet away.



Very quiet operation for a generator of this size and output.



Safe for use with sensitive electronic equipment.



Folding/locking handles and pneumatic wheels for convenient 1-person movement.



120 V/240 V capable for variable power requirements.



Discover the Powerhouse Difference at . . . [powerhouse-products.com](http://powerhouse-products.com).

# POWERHOUSE®

Powering life in the great outdoors.™

## PH6500Ri Specifications

AC Output: Rated / Max (Watts)	6000 / 6500 W
DC Output (A)	12 V – 8.3 A
Max Current (A)	54 A
Max Engine Speed	3600 rpm
Engine Type	Single Cylinder, 4-stroke OHV, Air Cooled Gasoline
Horse Power (hp) / Displacement	11.6 hp / 420 cc
Starting System	Remote, Electric
Continuous Run Time (hr) Full Load / ¼ Load per Tankful	5.3 hrs / 12.8 hrs
Fuel Tank Capacity (gal)	5.8 gal
Generator Dimension (in) (H x W x D)	29.5" x 28" x 32"
Dry Weight (lbs)	186 lbs
Noise Level, db @ 23': (Zero Load - Full Load)	73 / 78 dB
Rated Current (A)	50 A
Rated Frequency (Hz)	60 Hz
Rated Voltage (V)	120/240 V
Receptacles	One 120 V 20 A 5-20R Split Duplex, One 120 V 30 A L5-30R, One 120/240 V, 50 A L14-30R
Fuel Type	Unleaded Gasoline
Oil Capacity	37.2 oz
Oil Type	15W-40
Spark Plug	F7RTC
Automatic Low Oil Shutdown	Yes
Certifications	EPA, CARB, CETL, ISO 9001
Choke	Auto/Elec.
Fuel Economy Switch	Yes
Fuel Gauge	Yes
Hour Meter	Yes
Ignition System	Electronic Ignition
Inverter Equipped	Yes
Overload Reset Switch	Yes
Phase	Single
Remote Control	Yes
Structure	Enclosed
Handles/Wheels	Folding/locking wheelbarrow style handles; 2 Fixed, pneumatic wheels

Accessories Included:  
Oil Jug, 12V Charge Cable, Spare  
Spark Plug, Spark Plug Wrench.  
Spare Fuse, Keys & Remote



Two Year/1000 hours  
One Year/500 hours Commercial

POWERHOUSE Products  
DTS Manufacturing  
Wilsonville, OR 97070

salesinfo@powerhouse-products.com  
www.powerhouse-products.com

©2012 by POWERHOUSE Products.  
All rights reserved. 08/12 Rev. 1.0